




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶: A61M 27/00	A1	(11) International Publication Number: WO 99/01173 (43) International Publication Date: 14 January 1999 (14.01.99)
(21) International Application Number: PCT/EP98/04041 (22) International Filing Date: 30 June 1998 (30.06.98) (30) Priority Data: 1006457 3 July 1997 (03.07.97) NL (71) Applicant (for all designated States except US): POLY-MEDICS N.V. [BE/BE]; Ambachtslaan 1031, B-3990 Peer (BE). (72) Inventor; and (75) Inventor/Applicant (for US only): OHMSTEDE, Volkert, Simon [BE/BE]; Kloosterstraat 3B3, B-3910 Neerpelt (BE). (74) Agent: VAN KAN, J., J., H.; Algemeen Octrooibureau, World Trade Center, Past. Petersstraat 160, NL-5612 LV Eindhoven (NL).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: A DRAINAGE SYSTEM TO BE USED WITH AN OPEN WOUND, AN ELEMENT WHICH IS USED THEREBY FOR PLACING A DRAINAGE TUBE OR HOSE, AND A METHOD OF USING SAID DRAINAGE SYSTEM

**(57) Abstract**

The invention relates to a drainage system to be used with an open wound, which system consists of a block of a porous, moisture-absorbing material, which is connected to a tube or hose, which is in turn connected to a suction unit, which porous material is covered with a foil, wherein an element consisting of a plate-shaped member is provided on the porous, moisture-absorbing material, said plate-shaped member being provided on the upper side with a partially open thickening for placing or inserting the tube or hose, which thickening is provided on the underside with one or more openings, which open into and cooperate with openings in the plate-shaped member. The invention furthermore relates to said element and to a method of using the drainage system.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

A drainage system to be used with an open wound, an element which is used thereby for placing a drainage tube or hose, and a method of using said drainage system.

5 The invention relates to a drainage system to be used with an open wound, which system consists of a block of a porous, moisture-absorbing material, which is connected to a tube or hose, which is in turn connected to a suction unit, which porous material is covered with a foil. The invention furthermore relates to an element for placing a drainage
10 tube or hose, and to a method of using the drainage system.

 A drainage system of this kind is known from EP-A-0 620 720. According to said European patent application, a drainage system as shown in Figure 1 is used. A foam block is thereby placed in the open
15 wound, the foam block, which absorbs the wound fluid, is connected to a suction hose, and the whole consisting of the wound, the foam block and a part of the suction hose is covered with a foil. In this way wound fluid is withdrawn. In practice this known system has a few drawbacks, among
20 other things because the covering of the whole consisting of the wound, the foam block and the suction hose connected thereto with the foil is problematic.

 That is why attempts have been made to find an improved drainage system, and this has been accomplished by using a drainage system according to the invention. Said new drainage system is characterized in that an element consisting of a plate-shaped member is provided on the
25 porous, moisture-absorbing material, said plate-shaped member being provided on the upper side with a partially open thickening for placing or inserting the tube or hose therein, which thickening is provided on the underside with one or more openings, which open into and cooperate with openings in the plate-shaped member. Furthermore, the foil is
30 preferably affixed to the plate-shaped member, whereby said thickening is not covered.

 From EP-A-0 688 189 (which corresponds with WO 94/20041 in the name of the proprietor of EP-A-0 620 720) two wound treatment systems are known which work at a reduced pressure, whereby the system
35 as described in Figure 1 of EP-A-0 688 189 is an improvement in comparison with the drainage system as described in EP-A-0 620 720. The improvement consists of the fact that suction tube 12 is inserted into foam block 10,

which tube 12a is provided with one or more openings 14, which function to enable the withdrawal of wound fluid via hose 12. The improvement in accordance with the present invention consists of the fact that when the element according to the invention is used, the suction tube does not need
5 be inserted into the foam block which absorbs the wound fluid, but only needs to be connected to the open thickening which is present on the element. Furthermore, the foil can be easily affixed to the element according to the invention, without any risk of the foil coming into contact with the wound. The second embodiment according to EP-A-0 688 189
10 is shown in Figure 5 of the said European patent application. According to said Figure 5, a bell-shaped member provided with openings and with a suction tube is placed on a foam pad 120 which is present in the wound. A foil is draped over said bell-shaped member, which foil is drawn tighter against said bell-shaped member when a reduced pressure is applied. The
15 edges of the wound will be pulled inwardly under the influence of said reduced pressure, so that the wound will heal more quickly. The result of the application of said reduced pressure, however, is that no wound fluid is withdrawn via said foam pad and the hose which connects the reduced pressure source and the bell-shaped member. Accordingly, the
20 embodiment as shown in Figure 5 of EP-A-0 688 189 is different as regards design and purpose from the drainage system and the associated element according to the present invention.

The above embodiment as shown in Figure 5 of EP-A-0 688 189 is comparable with the drainage system which is described in
25 US patent No. 2,122,121 (1938). The drainage system known from US patent No. 2,122,121 is in particular intended for treating wounds resulting from urinary bladder operations. Accordingly, the drainage system is provided round the upper legs by means of bands 43 (Figure 1 of said US patent) and placed on the lower abdomen. A gauze package 40 is placed in the bell-
30 shaped member 1 as shown in Figure 4, which gauze package is screened by a perforated raised portion 16. Air is drawn in via said perforations and a ring line, and sucked out via pipe 30. The pieces of gauze that have absorbed wound fluid can be substituted for clean ones every day. The purpose of the system according to said US patent is to effect an air
35 circulation over the wound, whereby wound fluid is absorbed in the pieces of gauze, which wound fluid is not withdrawn via the vacuum system,

however, but which remains present in said pieces of gauze. This in contrast to the system and the element according to the invention.

US patents Nos. 3,572,340; 4,778,446 and 5,549,584 do not describe an element according to the present invention, nor do they describe the use of said element in a drainage system according to the present invention, therefore.

The element which can be used in the drainage system according to the invention is characterized in that it consists of a plate-shaped member, on which a partially open thickening is present, for applying or inserting a tube or a hose, which thickening is provided with one or more openings on the underside, which openings are in communication with the openings through the plate-shaped member. The openings through the plate-shaped member preferably continue into the thickening. The thickening is preferably closed at one end and open at the other end, so that a hose or a tube can be inserted into or applied on said open end.

The drainage system according to the invention is used for treating a chronic or acute wound by placing the porous block or a spongy, liquid-absorbing material made of a microporous foam on the wound. Then the element according to the invention is provided on the porous block, and the whole is covered with a foil, whereby the thickening on the element remains freely accessible for the tube or hose which is placed or inserted into or applied on the open end of said thickening. After the foil has been adhesively provided on the skin surrounding the wound, a reduced pressure can be applied under the foil, so that wound fluid can be withdrawn.

The invention will be explained in more detail in the description below, wherein reference is made to the appended drawing, wherein:

Figure 1 shows the drainage system known from EP-A-0 620 720;

Figure 2 shows the upper side of the element which is used in the drainage system according to the invention;

Figure 3 shows the underside of the element which is used in the drainage system according to the invention; and

Figure 4 diagrammatically shows the use of the drainage system according to the invention.

Figure 1 shows the known drainage system, wherein a wound 2 is present in skin 1. A block of a porous or foamy material 3 is placed on wound 2, which block is capable of absorbing wound fluid. A hose 4 is connected to porous material 3, which hose is connected to a suction pump. The direction of suction is indicated by arrow 6. The whole consisting of wound 2, block 3 and a part of hose 4 is covered with a foil 5, which is adhesively provided on the skin at points 7 and 8, so that a reduced pressure can be applied within the envelope formed by skin 1 and foil 5.

Figure 2 shows the upper side of element 10, which consists of a plate-shaped member 11 with the thickening 12 present thereon. Thickening 12 is open at one end 13, and closed at the other end 14. A tube can be inserted into the hollow thickening via opening 13, or a hose having the function of hose 4 in Figure 1 can be connected thereto. The foil indicated at 5 in Figure 1 may be affixed to plate-shaped member 11, so that said element and said foil are in one piece.

Figure 3 shows the bottom side of element 10, which consists of plate-shaped member 11 and the circumference of thickening 12. Openings 20 are present in the underside of plate-shaped member 11, which openings continue into thickening 12.

The underside of element 10 may be present on top of the block of porous material, whilst the foil may be provided on the upper side of said element, so that these three parts, which are essential for the proper functioning of the drainage system according to the invention may be integral with each other. This means a simplification of the method for using the drainage system, thus minimising the occurrence of mistakes in using a drainage system according to the invention.

Figure 4 diagrammatically shows the use of the drainage system according to the invention. Figure 4 shows an open wound 22 in skin 21 (the numerals correspond with those in Figure 1), in which wound a block 23 of a foamy material is present. Examples of said foamy material are polyvinyl alcohol and polyurethane. Present on block 23 is element 10, which consists of plate-shaped member 11 comprising thickening 12. Thickening 12 is provided with open end 13 and closed end 14. Openings 20 are provided through plate-shaped member 11, which openings open into the hollow space within thickening 12. Foil 25 is affixed to the upper side of plate-shaped member 11, which foil is also adhesively provided on

skin 21, at points 27 and 28. The hose or tube 24 is inserted into the open end 13 of thickening 12 and connected to suction unit 26. It will be apparent that the construction according to Figure 4 is much simpler to provide and safer to use, and that it provides a better seal on the skin and round the hose than the drainage system as shown in Figure 1.

Projections, guide ribs and the like may be provided on the underside of the element so as to provide a better guidance for the fluid from the upper side of the block of porous material to the openings present under the thickening. It is preferred to use a foil as described in Dutch patent application No. 1,005,726, which is marketed under the brand name Simpatex (Akzo).

In the simplest embodiment of the invention, the element is provided on the underside with a porous material, such as a spongy material of polyvinyl alcohol, and Simpatex (brand name) is affixed to the upper side of the element. Then the spongy material, on which the element and the foil are provided, is placed on the wound, and the foil is adhesively provided on the skin surrounding the wound. Then a hose is inserted into the thickening, and the hose is connected to a vacuum pump. Thus, a reduced pressure can be applied under the foil, and the wound fluid can be withdrawn.

CLAIMS

1. A drainage system to be used with an open wound, which system consists of a block of a porous, moisture-absorbing material, which is connected to a tube or hose, which is in turn connected to a suction unit, which porous material is covered with a foil, characterized in that an element consisting of a plate-shaped member is provided on the porous, moisture-absorbing material, said plate-shaped member being provided on the upper side with a partially open thickening for placing or inserting the tube or hose, which thickening is provided on the underside with one or more openings, which open into and cooperate with openings in the plate-shaped member.
2. A drainage system according to claim 1, characterized in that said foil is affixed to said element.
3. An element to be used in the drainage system according to claim 1, characterized in that it consists of a plate-shaped member, on which a partially open thickening is present, on or into which a tube or a hose can be applied or inserted, which thickening is provided with one or more openings on the underside, which openings are in communication with the openings through the plate-shaped member.
4. An element according to claim 3, characterized in that the openings in the plate-shaped member continue into said thickening.
5. An element according to claim 3 - 4, characterized in that said thickening is closed at one end, and that it is open at the other end, so that a hose or a tube can be inserted into or applied on said open end.
6. An element according to claims 3 - 5, characterized in that a foil is affixed to the upper side of the plate-shaped member, and that a block of a porous material is provided on the underside of said plate-shaped member.
7. A method of using the drainage system according to claim 1, characterized in that the element defined in claim 6, or successively the three parts, that is, said block-shaped porous material, said element and said foil are placed on the wound and said thickening is connected to a suction unit.

1/2




FIG.1

2/2




FIG. 2




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/EP 98/04041

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61M27/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2 122 121 A (ELMER) 28 June 1938 cited in the application see page 2, right-hand column, line 41 - page 3, left-hand column, line 13; figures ---	1-3,6
Y	WO 94 20041 A (WAKE FOREST UNIVERSITY) 15 September 1994 cited in the application see page 23, line 21 - page 24, line 23; figures ---	1-3,6
A	US 5 549 584 A (GROSS) 27 August 1996 cited in the application see the whole document ---	1,2
A	US 4 778 446 A (JENSEN) 18 October 1988 cited in the application see abstract; figures ---	1
-/--		



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

19 October 1998

Date of mailing of the international search report

27/10/1998

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Kousouretas, I

INTERNATIONAL SEARCH REPORT

Int. Patent Application No.
PCT/EP 98/04041

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 572 340 A (LLOYD) 23 March 1971 cited in the application see abstract; figures -----	1

INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/EP 98/04041

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2122121 A	28-06-1938	NONE	
WO 9420041 A	15-09-1994	US 5636643 A AU 696031 B AU 6360894 A EP 0688189 A JP 9503923 T	10-06-1997 27-08-1998 26-09-1994 27-12-1995 22-04-1997
US 5549584 A	27-08-1996	NONE	
US 4778446 A	18-10-1988	EP 0355186 A	28-02-1990
US 3572340 A	23-03-1971	NONE	